


Hitachi FX-Duo Interactive Whiteboard

Robust reliability that's truly hands on

Introducing the interactive whiteboard that's so versatile you can use either an electronic pen or finger.



The new DuoBoard also offers a hard, durable screen – not a membrane – that's hard to damage and that can be used by multiple users. It works as a dry-wipe board, too. In fact, the DuoBoard combines all the best features of all previous whiteboards, without limitations.

Until now, your interactive whiteboard came with a choice: electronic pen-driven or stylus/finger-driven.

Now you don't have to choose. The Hitachi FX-DuoBoard comes with a hard, damage-resistant screen. It responds to pen or finger. Its low-reflection surface is kind on the eyes. And it caters for multiple users at once. So, it's great for educational games.

Key Benefits

- Constant learning – robust surface means no downtime
- Flexible learning – can use finger or electronic pen
- Interactive group work – two or more can use board at once
- Kind to your eyes – low-reflection surface coating.

Redefining the interactive whiteboard

HITACHI
Inspire the Next

FX-Duo at a glance:


- Robust surface - The surface is robust and the whiteboard works even if there are scratches/dents on the surface.
- Low reflection - Projector reflection is minimized making it gentle on the eyes.
- Input Methods - use a finger/object or an electronic Pen to operate the whiteboard
- Simultaneous Inputs -Operate the whiteboard using both hands (gestures). Scroll and Zoom-in/Zoom-out.
- Field Replaceable Digitizer – A detachable digitiser makes it unnecessary to send the whole unit for repairing.
- Electronic Pen. Includes three side buttons

Specifications - FX-DUO-77

Model No.	AH00179
Input Methods:	Image sensor and infrared method
Interface to Computer:	USB 1.1, 2.0
Effective Screen Size	77 Inches (1,573 mm (W) x 1,180mm (H))
Sampling Rate	Approximately 100 points/sec
Resolution	Approximately 0.05 mm
Accuracy	Approximately ±1.5 mm
Board/Surface Material	Lauan wood + EPS (core), Colour steel boards (surface), Fluorine film (front surface coating)
Operating Specification	5 – 35 Celsius, 20 – 80% Humidity without condensation
Dimensions(mm)	1,743(W) x 1,357(H) x 56(D)
Dimensions w/ floor stand (mm)	1,743(W) x 1,824 – 2,174(H) x 620(D)
Weight (main unit)	24kg
Weight (w/ floor stand)	41kg
Packing dimension (main unit) (mm)	1,870(W) x 1,560(H) x 130(D)
(floor stand) (mm)	1,650(W) x 280(D) x 80(H)
Packing weight (main unit)	34kg
(floor stand)	18.5kg
Certificates	FCC, CE, UL
Warranty	Five-year limited equipment warranty upon registration. See hardware manual for details.

*1 The battery life varies according to the temperature and the usage environment. The life time of full recharging is approximately 500 times.

Further information:



Hitachi Software Engineering (UK) Limited
Interactive Media Solutions Division
Tel: +44 (0)207 246 6868
Fax: +44 (0)207 246 6860
Email: sales@hitachi-software.co.uk

Hitachi Software Engineering France S.A.S
Interactive Media Solutions Division
Tel: +33 (0)153 827 600
Fax: +33 (0)153 827 619
Email: starboard@hitachisoft-eu.com

Hitachi Software Engineering Europe AG
Interactive Media Solutions Division
Tel: +49 (0)30 8877 2600
Fax: +49 (0)30 8877 2610
Email: starboard@hitachisoft.de

www.hitachisoft-eu.com

HITACHI
Inspire the Next